

VX-P920 Series

P25 VHF/UHF Portable Radios

SPECIFICATION SHEET – NORTH AMERICA

Ready-To-Respond With P25 Interoperability

The conventional VX-P920 Series is ready to respond when you are with APCO P25 interoperability, state-of-the-art engineering and a wide array of features, providing great value in its class.

P25 Digital Mode Capabilities

Expanded Signaling: Supports selective calling, Talk Group IDs (TGID), Network Access Codes, Individual ID lists and Paging Group lists for flexible communications.

Secure Communication: Options available to support both Advanced Encryption Standard (AES) and Data Encryption Standard (DES) as required by APCO Project 25. Multiple encryption keys can also be stored in the radio.

Mixed Mode: Seamlessly switch between analog to P25 digital mode on each channel based on call type received and on programming for transmit.

Enhanced Voice Quality: Featuring the AMBE+2™ Vocoder, for exceptional voice quality. Suppresses background noise and improves clarity of radio transmission.

Connectivity Assurance: The RSSI indicator emits an audible alert when the receive signal strength drops to a level not suitable for reliable communications.

Loud Audio for Noisy Environments

With 700 mW audio output, be assured of hearing critical information you need in most situations.

Intrinsically Safe

Intrinsically safe models are SGS certified to the requirements of ANSI/UL913 5th Edition for use in Class I, II, III, Division I; Groups C, D, E, F, G; Temp T3C hazardous locations.

Never Miss An Important Call

Includes flexible scanning features designed to optimize operation. Along with basic scan, get Priority, Dual Watch, Follow-me, Follow-me Dual Watch and Talk Around scanning with a programmable home channel function built-in.

When Safety Counts – Never Be Alone

When help is needed, the VX-P920 Series has Emergency notification that will switch to a designated channel and send an emergency alert. The radios also include Remote Monitor which lets you monitor the situation happening near a target radio if someone is unresponsive.



VX-P929

VX-P924



The Vertex Standard Difference

Our number one goal is achieving superior customer satisfaction by delivering products and services that exceed your expectations. Vertex Standard radios are built to last and are backed by an industry-leading 3 year warranty.

VX-P920 Series

P25 VHF/UHF Portable Radios



SPECIFICATION SHEET – NORTH AMERICA

www.vertexstandard.com/lmr

Additional Features

- Field programmable (VX-P929)
- 10 programmable keys (VX-P929)
- 8 programmable keys (VX-P924)
- Programmable 3-position toggle key
- Direct channel recall
- 12-Character alpha-numeric display
- Minimum volume control
- User set mode

P25 Digital Mode Only

- Caller ID display
- BCLO and TOT

Analog Mode Only

- RX/TX Battery power save
- DTMF ANI / DTMF Paging
- Lone Worker
- 2-Tone Encode and Multi 2-Tone Decoding
- CTCSS/DCS Encode and Decode
- BCLO/BTLO and TOT
- MDC-1200® Encode (PTT ID, Emergency ID)
- Auto-Range Transpond System (ARTS™)
- Compander
- Clear voice and audio pitch control
- 7-Color LED (2-tone mode)
- User selectable tone
- Radio-to-radio cloning

Accessories

- MH-50D7A: Public Safety speaker mic with toggle†
- MH-66A7A: Submersible noise canceling speaker mic†
- MH-66B7A: Submersible speaker mic with PF key & toggle†
- VH-111: Over-the-head dual-muff headset
- VH-115L: Behind-the-head headset with boom mic
- VH-215L: Over-the-head single-muff headset
- FNB-VI29LI-UNI: 3000 mAh Li-Ion battery
- FNB-VI29LIIS-UNI: 3000 mAh Intrinsically safe Li-Ion battery
- FNB-VI28LI-UNI: 2300 mAh Li-Ion battery
- FNB-V87LIA: 2300 mAh Li-Ion battery
- FNB-VI27LI-UNI: 1380 mAh Li-Ion battery
- FNB-V86LIA: 1380 mAh Li-Ion battery
- FBA-34: Alkaline battery case (holds 6 AA batteries)
- VAC-UNI: Single unit charger for UNI batteries
- VAC-6058: Multi unit charger for UNI batteries
- VAC-921: Desktop rapid charger (non-UNI)
- VAC-6920: 6-Unit rapid charger (non-UNI)
- VCM-2: Vehicular charger kit for VAC-921
- LCC-920: Leather case options
- CLIP-17A: Swivel belt clip

VX-P920 Series Specifications

	VHF	UHF
General Specification		
Frequency Range	134 – 174 MHz	380 – 450 MHz; 450 – 512 MHz
Number of Channels and Groups	512 and 32 Groups	
Power Supply Voltage	7.4V DC ± 10%	
Channel Spacing	12.5 / 20* / 25* kHz	
PLL Steps	1.25 / 2.5 / 5 / 6.25 kHz	5 / 6.25 kHz
Battery Life P25 Mode (5-5-90 duty)		
3000 mAh FNB-VI29LI-UNI / FNB-VI29LIIS-UNI	19.7 hrs with saver / 15.6 hrs	18.7 hrs with saver / 14.3 hrs
2300 mAh FNB-VI28LI-UNI	16 hrs with saver / 12.4 hrs	15 hrs with saver / 11.5 hrs
2300 mAh FNB-V87LIA	16 hrs with saver / 12.4 hrs	15 hrs with saver / 11.5 hrs
1380 mAh FNB-VI27LI-UNI	9.6 hrs with saver / 7.5 hrs	9 hrs with saver / 6.9 hrs
1380 mAh FNB-V86LIA	9.6 hrs with saver / 7.5 hrs	9 hrs with saver / 6.9 hrs
IP Rating	IP 57	
Operating Temperature Range	-22°F to +140°F (-30°C to +60°C)	
Frequency Stability	±2.5 ppm	
RF Input-Output Impedance	50 Ohms	
Dimension (H x W x D)		
VX-P924 Model	5.3 x 2.3 x 1.6 in (133.0 x 57.5 x 40.5 mm) FNB-VI29LI-UNI (and IS) 5.3 x 2.3 x 1.6 in (133.0 x 57.5 x 40.5 mm) FNB-VI28LI-UNI 5.3 x 2.3 x 1.6 in (133.0 x 57.5 x 40.5 mm) FNB-V87LIA 5.3 x 2.3 x 1.4 in (133.0 x 57.5 x 35.0 mm) FNB-VI27LI-UNI 5.3 x 2.3 x 1.5 in (133.0 x 57.5 x 37.5 mm) FNB-V86LIA	
Weight (Approx.) with Antenna, Belt Clip		
VX-P924 Model	14.8 oz (420 g) FNB-VI29LI-UNI (and IS) 14.7 oz (416 g) FNB-VI28LI-UNI 11.4 oz (323 g) FNB-V87LIA 15.3 oz (433 g) FNB-VI27LI-UNI 13.1 oz (370 g) FNB-V86LIA	
Receiver Specification: measured by TIA/EIA-603, TIA-102 CAAA (Digital)		
Sensitivity 12dB SINAD	0.25 µV	0.32 µV
Digital 5% BER	0.25 µV	0.32 µV
Digital 1% BER	0.35 µV	0.40 µV
Adjacent Channel Selectivity (W/N)	75 dB / 70 dB	
Intermodulation	75 dB / 70 dB	
Spurious and Image Rejection	80 dB	75 dB
Audio Output	700 mW @ 16 Ohms, 5% THD	
Transmitter Specification: measured by TIA/EIA-603, TIA-102 CAAA (Digital)		
Output Power	5 / 2.5 / 1 / 0.25 W	
Modulation		
Analog	16K0F3E, 11K0F3E	
Digital	8K10F1D / 8K10F1E	
Spurious Emissions	70 dB	
FM Hum and Noise (W/N)	46 dB / 40 dB	
Audio Distortion	< 3% @ 1 kHz	

Applicable MIL-STD

Standard	Methods/Procedures			
	MIL 810C	MIL 810D	MIL 810E	MIL 810F
Low Pressure	500.1	500.2	500.3	500.4
High Temperature	501.1 / I, II	501.2 / I, II	501.3 / I, II	501.4 / I, II
Low Temperature	502.1 / I, II	502.2 / I, II	502.3 / I, II	502.4 / I, II
Temperature Shock	–	503.2 / I	503.3 / I	503.4 / I
Solar Radiation	505.1 / I	505.2 / II Cat. AI	505.3 / II Cat. AI	505.4 / I, II Cat. AI
Rain	506.1 / I	506.2 / I	506.3 / I, II	506.4 / I
Humidity	507.1 / I, II	507.2 / II, III	507.3 / II, III	–
Salt Fog	509.1	509.2	509.3	509.4
Dust	510.1 / I	510.2 / I	510.3 / I	510.4 / I, III
Vibration	514.2 / VIII, X	514.3 / I Cat. 10	514.4 / I Cat. 10	514.5 / I Cat. 20, 24
Shock	516.2 / I	516.3 / I	516.4 / I	516.5 / I

Specifications are subject to change without notice or obligation. Vertex Standard is a trademark of Vertex Standard LMR, Inc. All other trademarks are the property of their respective owners. †Intrinsically Safe system approved. Complete list of IS accessories in Owners Manual. *25 kHz will not be available on new equipment in the U.S.A. after 1/1/2013. © 2014 Vertex Standard LMR, Inc. All rights reserved. NSSP920_05/2014